

FIREPLACE FACTS

ODGSR36A AL FRESCO® SERIES

Outdoor 36 inch Radiant Gas Firebox.

FEATURES:

- 36" Fully Insulated Radiant Gas Outdoor Fireplace
- All Stainless Steel Construction
- Concrete Refractory Lining
- Stainless Steel Basket Grate, Stainless Mesh Firescreen
- Weather Resistant Insta-Flame Gas Burner System & Logs
- Flex line with cut off pre-installed
- Can be installed virtually anywhere where allowable by local building code
- NOT FOR INDOOR USE

MINIMUM FLOOR AREA:

- 41" W X 22¹/₂" D

HEARTH EXTENSION:

A Hearth Extension Is Recommended But **Not Required**

STANDARD GLASS DOORS:

- 36GDKSSSR - 36" Standard Bi-fold door kit - Stainless Steel Track

OPTIONAL ACCESSORIES:

- ODG36WE - Weather Enclosure for ODGSR36A
- UV36SH4 - 4" Stainless Steel Hood (For heater up to 40,000 BTU's and mantels 8" high by 12" wide)

GAS INLET & MANIFOLD PRESSURES

	Natural	LP
Minimum Inlet Pressure	5.5" w.c.	11.0" w.c.
Maximum Inlet Pressure	14.0" w.c.	14.0" w.c.
Manifold Pressure	3.5"w.c.	10.0" w.c.

CLEARANCES TO COMBUSTIBLES

Appliances

Top	0" (0 mm)
Bottom.....	0" (0 mm)
Side	0" (0 mm)
Back	0" (0 mm)
Perpendicular Sidewall	0" (0 mm)
Top of unit to ceiling	36" (914 mm)
Front of unit to combustibles.....	36" (914 mm)

ODGSR36A Certified to CSA 4-96

The Fireplace Facts Information Sheets are for quick reference only and are subject to change without notice. Actual fireplace instructions must abide by specifications provided with each product

